

# CP- UNR-4K2041-V2

4 Ch. 4K H.265 Network Video Recorder



## Main Features

- Support up to 4Ch. IP Camera Input
- H.265/H.264 dual codec decoding
- Up to 8MP resolution preview and playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 6TB, 2 USB ports(2.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



# CP- UNR-4K2041-V2

## 4 Ch. 4K H.265 Network Video Recorder



### Feature

Processor  
 IP Camera Input  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Output  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 OSD  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Smart Phone  
 Hard Disk  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Interface Ports  
 Record Interval  
 Max User Account  
 Ethernet  
 Protocols  
 Power Supply  
 Power Consumption  
 Working Temp

### Specification

Dual-core embedded processor  
 4 channel  
 Embedded LINUX  
 1 channel Input, 1 channel Output, RCA  
 GUI  
 1 HDMI, 1 VGA  
 H.265/H.264  
 3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768  
 Max 80 Mbps, 8MP/6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.  
 1/4  
 Camera title, Time, Camera lock, Motion detection, Recording  
 MD Zones: 396(22×18).  
 Supports  
 Supports  
 iPhone, iPad, Android Phone  
 1 SATA III ports, up to 6TB  
 Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips  
 Manual, Schedule (Regular (Continuous), MD, Stop  
 Time/Date, MD & Exact search (accurate to second)  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
 USB Device / Network  
 1 HDMI, 1 VGA, 2 USB Ports(2.0)  
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
 128 users  
 1 RJ-45 port (10/100Mbps)  
 HTTP, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search, ONVIF 2.4, CGI Conformant  
 DC12V/2A  
 <3W (without HDD)  
 -10 ~+55°C / 10~90%RH / 86~106kpa



 **CP- UNR-4K2041-V2****4 Ch. 4K H.265 Network Video Recorder****Feature**

Dimensions

Weight

**Specification**

260mm x 224.9mm x 47.6mm

0.8kg (without HDD)