

# CP- UNW-HP8G2-96

## 8 Port Fast Ethernet PoE Switch



### Main Features

- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- MAC auto learning, aging, MAC address capacity is 2K
- Supports MDI/MDIX self-adaptation
- Supports IEEE802.3af and IEEE803.3at power supply standards
- Layer two commercial switch
- RJ45 port supports 10/100/1000 Mbps self-adaptation
- Supports Hi-PoE 60W
- Adopts metal enclosure

# CP- UNW-HP8G2-96

## 8 Port Fast Ethernet PoE Switch

### Feature

Switch Capacity  
Packet Forwarding Rate  
MAC Address List  
Ethernet Port  
Packet Buffer  
PoE Power Consumption  
PoE Protocol  
Lightning Protection  
Power Source  
Operating Temperature  
Flow Control  
Humidity  
Dimensions  
Weight

### Specification

5.6Gbps  
4.17Mpps  
16K  
8 x 10/100Mbps PoE ports, 2 x 10/100/1000Mbps ports  
4Mb  
Port1≤60W, Port2-8≤30W, Total≤96W  
IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE  
Common Mode 2KV Differential Mode 0.5KV  
DC48~57V power adapter  
-10°C~+55°C  
Enable by default  
10%~90%  
190mm×100mm×30mm  
0.49kg